






**LINE FILTER**  
**UU16 SERIES**



**SPECIFICATIONS**

Part No.	Inductance (mH) Min	DC Resistance (Ω) Max	Rated Current ± (AC) A Max
UU 16-801	0.8	0.05	3.0
UU 16-132	1.3	0.07	2.5
UU 16-202	2.0	0.10	2.0
UU 16-502	5.0	0.20	1.5
UU 16-802	8.0	0.30	1.2
UU 16-133	13.0	0.48	1.0
UU16-183	18.0	0.70	0.8
UU 16-503	50.0	1.90	0.5

**ET24 SERIES**



**CHARACTERISTICS:**

- 1.Intended to be used in AC line filters for switching power supplies.
- 2.Provides much better filtering performance

**SPECIFICATIONS**

Part No.	Inductance (mH) Min	DC Resistance (Ω) Max	Rated Current ± (AC) A Max
ET 24-352	3.5	0.15	1.5
ET 24-432	4.3	0.19	1.2
ET 24-802	8.0	0.30	1.0
ET 24-113	11.0	0.45	0.8
ET 24-143	14.0	0.65	0.6
ET 24-223	22.0	1.00	0.5
ET 24-453	45.0	1.80	0.4
ET 24-733	73.0	3.00	0.3